

EMC TEST REPORT
For
SHENZHEN SRESKY CO.,LTD
Solar Light
Model No.: SSL series

Additional Model No.: ESL series, SCL series, SDL series, SGL series, SL series, SLL series, SML series, SWL series, SBC series, BLP series, Hubi series

Prepared for : SHENZHEN SRESKY CO.,LTD
Address : Jingmei Building, TaiWan industrial Park, SHIYAN Town,
BaoAn District, ShenZhen, China

Prepared by : Shenzhen Southern LCS Compliance Testing Laboratory Ltd.
Address : B Area, 1-2/F, Building B, Zhongyu Green High-tech
Industrial Park, Wenge Road, Heshuikou, Gongming Street,
Guangming New District, Shenzhen, Guangdong, China

Tel : (+86)755-29871520
Fax : (+86)755-29871521
Web : www.LCS-cert.com
Mail : webmaster@LCS-cert.com

Date of receipt of test sample : January 13, 2018
Number of tested samples : 1
Serial number : Prototype
Date of Test : January 13, 2018 ~ January 18, 2018
Date of Report : January 18, 2018



EMC TEST REPORT**EN 55015: 2013+A1: 2015**


Limits and methods of measurement of radio disturbance characteristics of electrical lighting and similar equipment

EN 61547: 2009


Equipment for general lighting purposes - EMC immunity requirements

Report Reference No.....: LCS180111028BE**Date Of Issue.....: January 18, 2018****Testing Laboratory Name.....: Shenzhen Southern LCS Compliance Testing Laboratory Ltd.****Address.....: B Area, 1-2/F, Building B, Zhongyu Green High-tech Industrial Park, Wenge Road, Heshuikou, Gongming Street, Guangming New District, Shenzhen, Guangdong, China****Testing Location/ Procedure.....: Full application of Harmonised standards ☒
Partial application of Harmonised standards ☐
Other standard testing method ☐****Applicant's Name.....: SHENZHEN SRESKY CO.,LTD****Address.....: Jingmei Building, TaiWan industrial Park, SHIYAN Town, BaoAn District, ShenZhen, China****Test Specification:****Standard.....: EN 55015: 2013+A1: 2015
EN 61547: 2009****Test Report Form No.....: LCSEMC-1.0****TRF Originator.....: Shenzhen Southern LCS Compliance Testing Laboratory Ltd.****Master TRF.....: Dated 2011-03****Shenzhen Southern LCS Compliance Testing Laboratory Ltd. All rights reserved.**

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen Southern LCS Compliance Testing Laboratory Ltd. is acknowledged as copyright owner and source of the material. Shenzhen Southern LCS Compliance Testing Laboratory Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Test Item Description.....: Solar Light**Trade Mark.....: N/A****Model/ Type Reference.....: SSL series****Ratings.....: DC 18V 1A****Result: Positive****Compiled by:**

Evan Fu/ File administrators

Supervised by:

Dm Gu/ Technique principal

Approved by:

Cherry Chen/ Manager

EMC -- TEST REPORT

Test Report No. : LCS180111028BE

January 18, 2018

Date of issue

Type/Model.....: SSL series

EUT.....: Solar Light

Applicant.....: SHENZHEN SRESKY CO.,LTDAddress.....: Jingmei Building, TaiWan industrial Park, SHIYAN Town,
BaoAn District, ShenZhen, China

Telephone.....: /

Fax.....: /

Manufacturer.....: SHENZHEN SRESKY CO.,LTDAddress.....: Jingmei Building, TaiWan industrial Park, SHIYAN Town,
BaoAn District, ShenZhen, China

Telephone.....: /

Fax.....: /

Factory.....: SHENZHEN SRESKY CO.,LTDAddress.....: Jingmei Building, TaiWan industrial Park, SHIYAN Town,
BaoAn District, ShenZhen, China

Telephone.....: /

Fax.....: /

Test Result according to the standards on page 7:**Positive**

The test report merely corresponds to the test sample.

It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

Revision History

Revision	Issue Date	Revisions	Revised By
00	January 18, 2018	Initial Issue	Cherry Chen

TABLE OF CONTENTS

Test Report Description	Page
1. SUMMARY OF STANDARDS AND RESULTS.....	7
1.1.Description of Standards and Results.....	7
1.2.Description of Performance Criteria.....	8
2. GENERAL INFORMATION.....	9
2.1.Description of Device (EUT).....	9
2.2.Description of Test Facility.....	9
2.3.Statement of the measurement uncertainty.....	9
2.4.Measurement Uncertainty.....	10
3. MEASURING DEVICES AND TEST EQUIPMENT.....	11
3.1.Radiated Electromagnetic Disturbance.....	11
3.2.Radiated Disturbance (Electric Field).....	11
3.3.Electrostatic Discharge.....	11
3.4.Power Frequency Magnetic Field Susceptibility.....	11
4. MAGNETIC FIELD EMISSION MEASUREMENT.....	12
4.1.Block Diagram of Test Setup.....	12
4.2.Magnetic Field Emission Measurement Standard and Limits.....	12
4.3.EUT Configuration on Test.....	12
4.4.Operating Condition of EUT.....	12
4.5.Test Procedure.....	13
4.6.Test Results.....	13
5. RADIATED EMISSION MEASUREMENT.....	15
5.1.Block Diagram of Test Setup.....	15
5.2.Test Standard.....	15
5.3.Radiated Emission Limits.....	15
5.4.EUT Configuration on Test.....	16
5.5.Operating Condition of EUT.....	16
5.6.Test Procedure.....	16
5.7.Test Results.....	16
6. ELECTROSTATIC DISCHARGE TEST.....	18
6.1.Block Diagram of Test Setup.....	18
6.2.Test Standard.....	18
6.3.Severity Levels and Performance Criterion.....	18
6.4.EUT Configuration on Test.....	18
6.5.Operating Condition of EUT.....	19
6.6.Test Procedure.....	19
6.7.Test Results.....	19
7. MAGNETIC FIELD IMMUNITY TEST.....	21
7.1.Block Diagram of Test Setup.....	21
7.2.Test Standard.....	21

7.3. Severity Levels and Performance Criterion.....	21
7.4. EUT Configuration on Test.....	21
7.5. Operating Condition of EUT.....	22
7.6. Test Procedure.....	22
7.7. Test Results.....	22
8. RF FIELD STRENGTH SUSCEPTIBILITY TEST.....	24
8.1. Block Diagram of Test Setup.....	24
8.2. Test Standard.....	24
8.3. Severity Levels and Performance Criterion.....	24
8.4. EUT Configuration on Test.....	25
8.5. Operating Condition of EUT.....	25
8.6. Test Procedure.....	25
8.7. Test Results.....	25
9. PHOTOGRAPH.....	27
9.1. Photo of Radiated Electromagnetic Disturbance Measurement.....	27
9.2. Photo of Radiated Measurement.....	27
9.3. Photo of Electrostatic Discharge Test.....	28
9.4. Photo of Magnetic Field Immunity Test.....	28
10. EXTERNAL AND INTERNAL PHOTOS OF THE EUT.....	29

1. SUMMARY OF STANDARDS AND RESULTS

1.1. Description of Standards and Results

The EUT have been tested according to the applicable standards as referenced below.

EMISSION (EN 55015: 2013+A1: 2015)			
Description of Test Item	Standard	Limits	Results
Conducted disturbance at mains terminals	EN 55015: 2013+A1: 2015	-----	N/A
Magnetic field emission	EN 55015: 2013+A1: 2015	-----	PASS
Radiated disturbance	EN 55015: 2013+A1: 2015	-----	PASS
Harmonic current emissions	EN 61000-3-2: 2014	Class C	N/A
Voltage fluctuations & flicker	EN 61000-3-3: 2013	-----	N/A
IMMUNITY (EN 61547: 2009)			
Description of Test Item	Basic Standard	Performance Criteria	Results
Electrostatic discharge (ESD)	EN 61000-4-2: 2009	B	PASS
Electrical fast transient (EFT)	EN 61000-4-4: 2012	B	N/A
Surge (Input a.c. power ports)	EN 61000-4-5: 2014	B	N/A
Radio-frequency, Continuous conducted disturbance	EN 61000-4-6: 2014	A	N/A
Power frequency magnetic field	EN 61000-4-8: 2010	A	PASS
Voltage dips, 30% reduction	EN 61000-4-11: 2004	C	N/A
Voltage interruptions		B	N/A
N/A is an abbreviation for Not Applicable.			

1.2. Description of Performance Criteria

General Performance Criteria

Examples of functions defined by the manufacturer to be evaluated during testing include, but are not limited to, the following:

- essential operational modes and states;
- tests of all peripheral access (hard disks, floppy disks, printers, keyboard, mouse, etc.);
- quality of software execution;
- quality of data display and transmission;
- quality of speech transmission.

1.2.1. Performance criterion A

The equipment shall continue to operate as intended without operator intervention. No degradation of performance or loss of function is allowed below a performance level specified by the manufacture when the equipment is used as intended. The performance level may be replaced by a permissible loss of performance. If the minimum performance level or the permissible performance loss is not specified by the manufacturer, then either of these may be deliver from the product description and documentation, and by what the user may reasonably expect from the equipment if used as intended.

1.2.2. Performance criterion B

After the test, the equipment shall continue to operate as intended without operator intervention. No degradation of performance or loss of function is allowed, after the application of the phenomena below a performance level specified by the manufacture, when the equipment is used as intended. The performance level may be replaced by a permissible loss of performance.

During the test, degradation of performance is allowed. However, no change of operation state or stored data is allowed to persist after the test.

If the minimum performance level (or the permissible performance loss) is not specified by the manufacturer, then either of these may be deliver from the product description and documentation, and by what the user may reasonably expect from the equipment if used as intended.

1.2.3. Performance criterion C

Loss of function is allowed, provided the function is self-recoverable, or can be restored by the operation of the controls by the user in accordance with the manufacture's instructions. Functions, and/or information stored in non-volatile memory, or protected by a battery backup, shall not be loss.

2. GENERAL INFORMATION

2.1. Description of Device (EUT)

EUT	: Solar Light
Trade Mark	: N/A
Model Number	: SSL series
Power Supply	: DC 18V 1A

2.2. Description of Test Facility

Site Description EMC Lab.	: TUV RH Registration Number. is UA 50362241 0001. UL Registration Number. is 100571-492. NVLAP Registration Number. is 600112-0.
------------------------------	-----------------------------------------------------------------------------------------------------------------------------------------

Test Facilities	Shenzhen Southern LCS Compliance Testing Laboratory Ltd. B Area, 1-2/F, Building B, Zhongyu Green High-tech Industrial Park, Wenge Road, Heshuikou, Gongming Street, Guangming New District, Shenzhen, Guangdong, China
-----------------	----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

RF Field Strength Susceptibility	Shenzhen LCS Compliance Testing Laboratory Ltd. 1F., Xingyuan Industrial Park, Tongda Road, Bao'an Avenue., Bao'an District, Shenzhen, Guangdong, China
-------------------------------------	---------------------------------------------------------------------------------------------------------------------------------------------------------------

2.3. Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. To CISPR 16 – 4 “Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements” and is documented in the LCS quality system acc. To DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

2.4.Measurement Uncertainty

Test	Parameters	Expanded uncertainty (U_{lab})	Expanded uncertainty (U_{Cispr})
Conducted Emission	Level accuracy (9kHz to 150kHz) (150kHz to 30MHz)	± 1.40 dB ± 2.80 dB	± 4.0 dB ± 3.6 dB
Electromagnetic Radiated Emission (3-loop)	Level accuracy (9kHz to 30MHz)	± 3.46 dB	N/A
Radiated Emission	Level accuracy (9kHz to 30MHz)	± 3.12 dB	N/A
Radiated Emission	Level accuracy (30MHz to 200MHz)	± 4.66 dB	± 5.2 dB
Radiated Emission	Level accuracy (200MHz to 1000MHz)	± 4.64 dB	± 5.0 dB
Mains Harmonic	Voltage	$\pm 0.640\%$	N/A
Voltage Fluctuations & Flicker	Voltage	$\pm 0.530\%$	N/A

- (1) Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus.
- (2) The reported expanded uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor of $k=2$, which for a normal distribution corresponds to a coverage probability of approximately 95%.

3. MEASURING DEVICES AND TEST EQUIPMENT

3.1. Radiated Electromagnetic Disturbance

Item	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal.
1	EMI Test Receiver	ROHDE & SCHWARZ	ESR 7	101142	2017-06-18
2	EMI Test Receiver	ROHDE & SCHWARZ	ESPI3	101840	2017-06-18
3	Triple-loop Antenna	LAPLACE	MK II-A	9161	2017-06-18
4	10dB Attenuator	LAPLACE	HAT-10	15542	2017-06-18
5	EMI Test Software	AUDIX	E3	N/A	N/A

3.2. Radiated Disturbance (Electric Field)

Item	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal.
1	3m Semi Anechoic Chamber	SIDT FRANKONIA	SAC-3M	03CH03-HY	2017-06-18
2	EMI Test Receiver	ROHDE & SCHWARZ	ESR 7	101181	2017-06-18
3	Log per Antenna	SCHWARZBECK	VULB9163	9163-470	2016-04-18
4	EMI Test Software	AUDIX	E3	N/A	2017-06-18
5	Positioning Controller	MF	MF-7082	/	2017-06-18

3.3. Electrostatic Discharge


Item	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal.
1	ESD Simulator	SCHLODER	SESD 230	604035	2017-06-18

3.4. Power Frequency Magnetic Field Susceptibility

Item	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal.
1	Power frequency mag-field generator System	EVERFINE	EMS61000-8K	906003	2017-06-18

4. MAGNETIC FIELD EMISSION MEASUREMENT

4.1. Block Diagram of Test Setup



4.2. Magnetic Field Emission Measurement Standard and Limits

4.2.1. Test Standard

EN 55015: 2013+A1: 2015

4.2.2. Test Limits

Frequency	Limits for loop diameter (dB μ A)
	2m
9kHz ~ 70kHz	88
70kHz ~ 150kHz	88 ~ 58*
150kHz ~ 3.0MHz	58 ~ 22*
3.0MHz ~ 30MHz	22

1. At the transition frequency the lower limit applies.
2. * decreasing linearly with logarithm of the frequency.

4.3. EUT Configuration on Test

The configuration of the EUT is same as Section 3.3.

4.4. Operating Condition of EUT

Same as conducted measurement which is listed in Section 4.4, except the test set up replaced by Section 4.1.

4.5. Test Procedure

The EUT is placed on a wood table in the center of a loop antenna. The induced current in the loop antenna is measured by means of a current probe and the test receiver. Three field components are checked by means of a coaxial switch.

The frequency range from 9kHz to 30MHz is investigated. The receiver is measured with the quasi-peak detector. For frequency band 9kHz to 150kHz, the bandwidth of the field strength meter is set at 200Hz. For frequency band 150kHz to 30MHz, the bandwidth is set at 9kHz.


All the test results are listed in Section 4.6.

4.6. Test Results

PASS.

The frequency range from 9kHz to 30MHz is investigated.


Model No.	SSL series	Test Mode	ON
Environmental Conditions	24°C, 56% RH	Test Engineer	MUNDO ZHOU
Pol	X		



	Freq	Reading	LISNFac	CabLos	Measured	Limit	Over	Remark
	MHz	dBuA	dB	dB	dBuA	dBuA	dB	
1	3.20	-44.07	55.79	0.70	12.42	22.00	-9.58	QP
2	5.51	-45.27	51.70	0.73	7.16	22.00	-14.84	QP
3	6.74	-43.01	49.93	0.76	7.68	22.00	-14.32	QP
4	10.71	-42.21	48.16	0.82	6.77	22.00	-15.23	QP
5	15.93	-38.66	47.31	0.85	9.50	22.00	-12.50	QP
6	21.69	-36.79	46.18	0.87	10.26	22.00	-11.74	QP

Remarks: 1. Measured = Reading + Cable Loss.
2. The emission levels that are 20dB below the official limit are not reported.


Model No.	SSL series	Test Mode	ON
Environmental Conditions	24°C, 56% RH	Test Engineer	MUNDO ZHOU
Pol	Y		



	Freq	Reading	LISNFac	CabLos	Measured	Limit	Over	Remark
	MHz	dBuA	dB	dB	dBuA	dBuA	dB	
1	3.15	-48.69	55.89	0.70	7.90	22.00	-14.10	QP
2	5.64	-47.51	51.49	0.74	4.72	22.00	-17.28	QP
3	9.10	-45.49	48.64	0.80	3.95	22.00	-18.05	QP
4	12.90	-42.29	47.80	0.83	6.34	22.00	-15.66	QP
5	19.36	-38.90	46.70	0.86	8.66	22.00	-13.34	QP
6	28.57	-35.92	44.75	0.90	9.73	22.00	-12.27	QP

Remarks: 1. Measured = Reading + Cable Loss.
2. The emission levels that are 20dB below the official limit are not reported.

Model No.	SSL series	Test Mode	ON
Environmental Conditions	24°C, 56% RH	Test Engineer	MUNDO ZHOU
Pol	Z		




	Freq	Reading	LISNFac	CabLos	Measured	Limit	Over	Remark
	MHz	dBuA	dB	dB	dBuA	dBuA	dB	
1	1.98	-49.64	58.51	0.68	9.55	26.99	-17.44	QP
2	3.73	-48.86	54.90	0.71	6.75	22.00	-15.25	QP
3	5.78	-46.64	51.28	0.74	5.38	22.00	-16.62	QP
4	11.33	-43.57	48.05	0.82	5.30	22.00	-16.70	QP
5	13.55	-40.43	47.70	0.83	8.10	22.00	-13.90	QP
6	22.04	-40.91	46.10	0.87	6.06	22.00	-15.94	QP

Remarks: 1. Measured = Reading + Cable Loss.
2. The emission levels that are 20dB below the official limit are not reported.

5. RADIATED EMISSION MEASUREMENT

5.1. Block Diagram of Test Setup



5.2. Test Standard

EN 55015: 2013+A1: 2015

5.3. Radiated Emission Limits

All emanations from a class B device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified below:

FREQUENCY (MHz)	DISTANCE (Meters)	FIELD STRENGTHS LIMIT (dB μ V/m)
30 ~ 230	3	40
230 ~ 300	3	47

- Note: (1) The smaller limit shall apply at the combination point between two frequency bands.
- (2) Distance refers to the distance in meters between the measuring instrument antenna and the closed point of any part of the EUT.

5.4.EUT Configuration on Test

The EN 55015 regulations test method must be used to find the maximum emission during radiated emission measurement.

5.5.Operating Condition of EUT

5.5.1 Turn on the power.

5.5.2 After that, let the EUT work in test mode (ON) and measure it.

5.6.Test Procedure

The EUT is placed on a turntable, which is 0.8 meter high above the ground. The turntable can rotate 360 degrees to determine the position of the maximum emission level. The EUT is set 3 meters away from the receiving antenna, which is mounted on an antenna tower. The antenna can be moved up and down from 1 to 4 meters to find out the maximum emission level. By-log antenna (calibrated by Dipole Antenna) is used as a receiving antenna. Both horizontal and vertical polarization of the antenna is set on test.

The bandwidth of the Receiver is set at 120kHz.


The frequency range from 30MHz to 300MHz is investigated.

5.7.Test Results

PASS.

The test result please refer to the next page.

Model No.	SSL series	Test Mode	ON
Environmental Conditions	24°C, 56% RH	Detector Function	Quasi-peak
Pol	Vertical	Distance	3m
Test Engineer	MUNDO ZHOU		




	Freq	Reading	CabLos	Antfac	Measured	Limit	Over	Remark
	MHz	dBuV	dB	dB/m	dBuV/m	dBuV/m	dB	
1	37.68	5.18	0.38	12.99	18.55	40.00	-21.45	QP
2	52.74	4.33	0.46	13.12	17.91	40.00	-22.09	QP
3	62.97	3.24	0.48	11.51	15.23	40.00	-24.77	QP
4	95.97	4.74	0.58	12.90	18.22	40.00	-21.78	QP
5	110.18	2.97	0.61	12.22	15.80	40.00	-24.20	QP
6	181.18	3.41	0.89	9.78	14.08	40.00	-25.92	QP

Note: 1. All readings are Quasi-peak values.

2. Measured= Reading + Antenna Factor + Cable Loss

3. The emission that are 20db below the official limit are not reported

Model No.	SSL series	Test Mode	ON
Environmental Conditions	24°C, 56% RH	Detector Function	Quasi-peak
Pol	Horizontal	Distance	3m
Test Engineer	MUNDO ZHOU		



	Freq	Reading	CabLos	Antfac	Measured	Limit	Over	Remark
	MHz	dBuV	dB	dB/m	dBuV/m	dBuV/m	dB	
1	52.37	5.83	0.46	13.14	19.43	40.00	-20.57	QP
2	59.04	2.84	0.49	12.75	16.08	40.00	-23.92	QP
3	97.75	3.48	0.61	13.02	17.11	40.00	-22.89	QP
4	114.06	3.21	0.65	11.53	15.39	40.00	-24.61	QP
5	169.48	3.58	0.80	8.95	13.33	40.00	-26.67	QP
6	195.04	3.91	0.96	10.57	15.44	40.00	-24.56	QP


Note: 1. All readings are Quasi-peak values.

2. Measured= Reading + Antenna Factor + Cable Loss

3. The emission that are 20db below the official limit are not reported

6. ELECTROSTATIC DISCHARGE TEST

6.1. Block Diagram of Test Setup



6.2. Test Standard

EN 61547: 2009 (EN 61000-4-2: 2009, Severity Level: Air Discharge: Level 3, $\pm 8\text{KV}$
Contact Discharge: Level 2, $\pm 4\text{KV}$)

6.3. Severity Levels and Performance Criterion

6.3.1. Severity level

Level	Test Voltage Contact Discharge (KV)	Test Voltage Air Discharge (KV)
1.	± 2	± 2
2.	± 4	± 4
3.	± 6	± 8
4.	± 8	± 15
X	Special	Special

6.3.2. Performance criterion: **B**

6.4. EUT Configuration on Test

The configuration of EUT is listed in Section 3.6

6.5. Operating Condition of EUT

- 6.5.1. Setup the EUT as shown in Section 6.1.
- 6.5.2. Turn on the power of all equipments.
- 6.5.3. Let the EUT work in test mode (ON) and measure it.

6.6. Test Procedure

6.6.1. Air Discharge

This test is done on a non-conductive surfaces. The round discharge tip of the discharge electrode shall be approached as fast as possible to touch the EUT. After each discharge, the discharge electrode shall be removed from the EUT. The generator is then re-triggered for a new single discharge and repeated 10 times for each pre-selected test point. This procedure shall be repeated until all the air discharge completed.

Because the case of the EUT is metal surface, so it does not need to be tested.

6.6.2. Contact Discharge

All the procedure shall be same as Section 9.6.1. except that the tip of the discharge electrode shall touch the EUT before the discharge switch is operated.

6.6.3. Indirect Discharge For Horizontal Coupling Plane

At least 20 single discharges shall be applied to the horizontal coupling plane, at points on each side of the EUT. The discharge electrode positions vertically at a distance of 0.1m from the EUT and with the discharge electrode touching the coupling plane.

6.6.4. Indirect Discharge For Vertical Coupling Plane

At least 20 single discharge shall be applied to the center of one vertical edge of the coupling plane. The coupling plane, of dimensions 0.5m X 0.5m, is placed parallel to, and positioned at a distance of 0.1m from the EUT. Discharges shall be applied to the coupling plane, with this plane in sufficient different positions that the four faces of the EUT are completely illuminated.

6.7. Test Results

PASS.

Please refer to the following page.


Electrostatic Discharge Test Results

Standard	<input type="checkbox"/> IEC 61000-4-2 <input checked="" type="checkbox"/> EN 61000-4-2		
Applicant	SHENZHEN SRESKY CO.,LTD		
EUT	Solar Light	Temperature	23℃
M/N	SSL series	Humidity	56%
Criterion	B	Pressure	1021mbar
Test Mode	ON	Test Engineer	MUNDO ZHOU

Air Discharge						
Test Points	Test Levels			Results		
	± 2KV	± 4KV	± 8KV	Pass	Fail	Performance Criterion
Front	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/> A <input checked="" type="checkbox"/> B
Back	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/> A <input checked="" type="checkbox"/> B
Left	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/> A <input checked="" type="checkbox"/> B
Right	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/> A <input checked="" type="checkbox"/> B
Top	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/> A <input checked="" type="checkbox"/> B
Bottom	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/> A <input checked="" type="checkbox"/> B
Contact Discharge						
Test Points	Test Levels		Results			
	± 2 KV	±4 KV	Pass	Fail	Performance Criterion	
Front	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/> A	<input checked="" type="checkbox"/> B
Back	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/> A	<input checked="" type="checkbox"/> B
Left	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/> A	<input checked="" type="checkbox"/> B
Right	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/> A	<input checked="" type="checkbox"/> B
Top	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/> A	<input checked="" type="checkbox"/> B
Bottom	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/> A	<input checked="" type="checkbox"/> B
Discharge To Horizontal Coupling Plane						
Side of EUT	Test Levels		Results			
	± 2 KV	± 4 KV	Pass	Fail	Performance Criterion	
Front	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/> A	<input checked="" type="checkbox"/> B
Back	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/> A	<input checked="" type="checkbox"/> B
Left	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/> A	<input checked="" type="checkbox"/> B
Right	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/> A	<input checked="" type="checkbox"/> B
Discharge To Vertical Coupling Plane						
Side of EUT	Test Levels		Results			
	± 2 KV	± 4 KV	Pass	Fail	Performance Criterion	
Front	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/> A	<input checked="" type="checkbox"/> B
Back	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/> A	<input checked="" type="checkbox"/> B
Left	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/> A	<input checked="" type="checkbox"/> B
Right	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/> A	<input checked="" type="checkbox"/> B

7. MAGNETIC FIELD IMMUNITY TEST

7.1. Block Diagram of Test Setup



7.2. Test Standard

EN 61547: 2009 (EN 61000-4-8: 2010, Severity Level 2: 3 A/m)

7.3. Severity Levels and Performance Criterion

7.3.1. Severity level

Level	Magnetic Field Strength (A/m)
1.	1
2.	3
3.	10
4.	30
5.	100
X	Special

7.3.2. Performance criterion: A

7.4. EUT Configuration on Test

The configuration of EUT are listed in Section 3.10.

7.5.Operating Condition of EUT

7.5.1.Setup the EUT as shown in Section 7.1.

7.5.2.Turn on the power of all equipments.

7.5.3.Let the EUT work in test mode (On) and measure it.

7.6.Test Procedure

7.6.1.Set up the EUT system as shown on Section 7.1.

7.6.2.The Induction coil is set up in horizontal or vertical.

7.6.3.Let the EUT work in test mode and measure it.

7.7.Test Results

PASS.

Please refer to the following page.

Magnetic Field Immunity Test Result


Standard	<input type="checkbox"/> IEC 61000-4-8 <input checked="" type="checkbox"/> EN 61000-4-8		
Applicant	SHENZHEN SRESKY CO.,LTD		
EUT	Solar Light	Temperature	23℃
M/N	SSL series	Humidity	56%
Test Mode	ON	Criterion	A
Test Engineer	MUNDO ZHOU		

Test Level (A/M)	Testing Duration	Coil Orientation	Criterion	Result
3	5 mins	X	A	PASS
3	5 mins	Y	A	PASS
3	5 mins	Z	A	PASS

Note:

8. RF FIELD STRENGTH SUSCEPTIBILITY TEST

8.1. Block Diagram of Test Setup



8.2. Test Standard

EN 61547: 2009 (EN 61000-4-3: 2006+A2: 2010, Severity Level: 2, 3V / m)

8.3. Severity Levels and Performance Criterion

8.3.1. Severity level

Level	Field Strength (V/m)
1	1
2	3
3	10
X	Special

8.3.2. Performance criterion: A

8.4.EUT Configuration on Test

The configuration of EUT are listed in Section 3.13.

8.5.Operating Condition of EUT

8.5.1.Setup the EUT as shown in Section 8.1.

8.5.2.Turn on the power of all equipments.

8.5.3.Let the EUT work in test mode (On) and measure it.

8.6.Test Procedure

The EUT and its simulators are placed on a turn table which is 0.8 meter above ground. EUT is set 3 meter away from the transmitting antenna which is mounted on an antenna tower. Both horizontal and vertical polarization of the antenna are set on test. Each of the four sides of EUT must be faced this transmitting antenna and measured individually. In order to judge the EUT performance, a CCD camera is used to monitor EUT screen. All the scanning conditions are as follows:

Condition of Test	Remarks
-----	-----
1. Fielded Strength	3 V/m (Severity Level 2)
2. Radiated Signal	Unmodulated
3. Scanning Frequency	80 - 1000 MHz
4. Dwell time of radiated	0.0015 decade/s
5. Waiting Time	3 Sec.

8.7.Test Results

PASS.

Please refer to the following page.

RF Field Strength Susceptibility Test Results

Standard	<input type="checkbox"/> IEC 61000-4-3 <input checked="" type="checkbox"/> EN 61000-4-3		
Applicant	SHENZHEN SRESKY CO.,LTD		
EUT	Solar Light	Temperature	26℃
M/N	SSL series	Humidity	51%
Field Strength	3 V/m	Criterion	A
Test Mode	ON	Test Engineer	MUNDO ZHOU
Frequency Range	80 MHz to 1000 MHz		
Modulation	<input type="checkbox"/> None <input type="checkbox"/> Pulse <input checked="" type="checkbox"/> AM 1KHz 80%		
Steps	1%		

	Horizontal	Vertical
Front	PASS	PASS
Right	PASS	PASS
Rear	PASS	PASS
Left	PASS	PASS

Test Equipment:

1. Signal Generator: 2031 (MARCONI)
2. Power Amplifier: 500A100 & 100W/1000M1 (A&R)
3. Power Antenna: 3108 (EMCO) & AT1080 (A&R)
4. Field Monitor: FM2000 (A&R)


Note:

9. PHOTOGRAPH

9.1. Photo of Radiated Electromagnetic Disturbance Measurement



9.2. Photo of Radiated Measurement



9.3. Photo of Electrostatic Discharge Test



9.4. Photo of Magnetic Field Immunity Test



10. EXTERNAL AND INTERNAL PHOTOS OF THE EUT



Fig. 1




Fig. 2

-----THE END OF TEST REPORT-----